

Indirect Fired Heaters

DEPENDABLE HEAT
When and Where you Need it



FVP-400



FVO-400

- **Indirect fired heat exchanger allows external exhaust of combustion products**
- **Power supply indicator to pre determine any power issues**
- **Thermostatically controlled (optional)**
- **Standard steel lifting harness**
- **Heavy duty pneumatic tubed tires and slim design provides for easy site mobility and transportation**
- **FVO-400 model has a built in fuel tank with fuel gauge**

flagro
USA INC.

Indirect Fired Heaters

OIL, NATURAL GAS, PROPANE

Model:	FVO-400 Oil	FVN-400 Natural Gas	FVP-400 Propane
Heat Capacity	390,000 BTU's	390,000 BTU's	390,000 BTU's
Fuel Tank Capacity	42 US Gallons	External N/A	External N/A
Operation Time/ Fuel consumption	15 Hours 2.75 Gallons/Hour	380 CFH	4.26 GPH
Dimensions	70" L 29" W 52" H	70" L 29" W 47" H	70" L 29" W 47" H
Heat Exchanger	16 Gauge	16 Gauge	16 Gauge
Fan Motor	3/4 HP @1725 RPM 2500 CFM	3/4 HP @1725 RPM 2500 CFM	3/4 HP @1725 RPM 2500 CFM
Ignition	Direct Spark Igniter	Direct Spark Igniter	Direct Spark Igniter
Nozzle Size/Gas Pressure	2.25 U.S. GPH @150 PSI	2.0" W.C.	3.2" W.C.
Air Outlet (optional)	Two 12 Inch Diameter One 16 Inch Diameter	Two 12 Inch Diameter One 16 Inch Diameter	Two 12 Inch Diameter One 16 Inch Diameter
Wheels	Two 16" Pneumatic tubed wheels	Two 16" Pneumatic tubed wheels	Two 16" Pneumatic tubed wheels
Power Requirement	115V/60Hz/1Ph/15 Amp	115V/60Hz/1Ph/15 Amp	115V/60Hz/1Ph/15 Amp
Approvals	cETLus	cETLus	cETLus
Weight	450 lbs	365 lbs	365 lbs

OPTIONS

FV-D12



12 inch X 12 Ft Flexible Ducting

FV-THA



Remote Thermostat Control
c/w 25 ft Cord

14501 Judicial Road, Suite 40, Burnsville, MN 55306
 PHONE: 952-898-2881 (866) 266-2484
 FAX: 952-898-6693 E-MAIL: info@flagrousa.com
www.flagrousa.com

flagro
 USA INC.